



## CATALOG

Zikuñaga Bailara 17, B  
20120 Hernani, Gipuzkoa

Tel. +34 94355 54 65

[www.totemmt.com](http://www.totemmt.com)

[info@totemcams.com](mailto:info@totemcams.com)

# Totem Cam



Reference	Color	Strength	Range Min	Range Max	Weight
Totem Cam 0.50	black	6kN	11,7mm	18,9mm	69g
Totem Cam 0.65	blue	8kN	13,8mm	22,5mm	75g
Totem Cam 0.80	yellow	9kN	17mm	27,7mm	83g
Totem Cam 1.00	purple	10kN	20,9mm	34,2mm	95g
Totem Cam 1.25	green	13kN	25,7mm	42,3mm	109g
Totem Cam 1.50	red	13kN	31,6mm	52,2mm	132g
Totem Cam 1.80	orange	13kN	39,7mm	64,2mm	144g

- The most versatile. Broadened placement possibilities.
- Patented Direct Loading System (US Pat. 7,014,156). High holding power.
- Narrowest head for pockets and shallow cracks.
- High flexibility. Very stable once placed.
- Possibility to load only two lobes on shallow cracks.
- Great expansion range 1.64:1
- Light and durable.
- 7 sizes. CE certified and individually tested.

